

ATH Cross Lift 40 OGA

Product Images



Description

- High quality and robust hydraulic drive platforms scissor lift who require minimal maintenance
- Powerful hydraulic unit with load-dependent lowering speed controller
- Suitable installation on-ground with inclusive Kit for surface mounting
- With recesses for turning plates in the front and mechanically lockable sliding plates in the back, free-wheel lift (loading capacity: 4 t, lifting height: 450 mm), including rails for the optional rolling bridge jack, pluggable platforms-connections beams, incl. metal protections covers and switch for the optional 24V LED Lighting.
- Pneumatic unlocking of the safety locks, CE-Stop and acoustic signal through lowering
- Emergency lowering device for lowering in case of power failure, monitoring of safety synchronization by light barrier.
- Ideally suited for inspection, wheel alignment, repairing jobs and testing stations for driver assistance systems

Additional Information

Color	anthracite-grey / black
Rated load capacity	4.000 kg
Lifting height max.	2.160 mm
Drive-on-height	295 mm
Total platform length	4.230 mm
Total platform width	600 mm
Driving power	3,5 kW
Lifting/Lowering time	ca. 70 s
Power supply voltage	3x 400V / C16A
Concrete strength	min. C20/25 5.500 x 3.000 x 200 mm

