

# ATH W44 P

## Product Images

---



## Description

---

- **Pneumatic shaft:** 40 mm clamping shaft for quick and secure wheel clamping
- **Sonar technology:** Non-contact rim width detection
- **Automatic positioning:** Automatically positions the wheel for weight attachment
- **Extended clamping shaft:** Additional clamping shaft for use with other clamping devices
- **Laser indicator:** Enables precise placement of the clamping weights at the 5 o'clock position
- **Static/Dynamic program:** Enables optimal balancing at different speeds
- **Alu balancing programs:** Special programs for aluminum rims to improve balancing quality
- **Split rear spoke weight positioning:** Enables precise weight distribution behind the spokes
- **Optimization program:** Program for fine-tuning and optimizing the balancing process
- **Optional motorcycle function:** Additional function for balancing motorcycle wheels

## Additional Information

---

|                            |             |
|----------------------------|-------------|
| Center hole diameter rim   | 45 – 130 mm |
| Measuring time car   truck | 8 s         |
| Measurement tolerance      | +/- 1g      |
| Measuring speed            | 200 U/min   |
| Rim width                  | 1,5" – 20"  |
| Rim diameter               | 10" – 24"   |
| Max. wheel diameter        | 900 mm      |
| Wheel weight max.          | 65 kg       |
| Compressed air connection  | 6 bar       |
| Monitor                    | 22" LED     |
| Driving power              | 0,20 kW     |
| Power supply voltage       | 230V / C16A |

