

ATH M74Z PLUS

Product Images



Short Description

The ATH M74Z Plus is the modern tire changer for maximum efficiency. The new A74 assist arm with additional bead-breaking function makes work easier. The integrated camera in the assist arm displays the wheel underside directly on the control panel for full control. The height-adjustable center

hole clamping with flange and quick-lock nut ensures precise mounting. Perfect for workshops that value speed and convenience.

Description

- Rear swivel with pneumatic mounting head clamping including automatic vertical and horizontal rim removal
- Control via ergonomically arranged foot pedals
- Including pneumatic controlled auxiliary assembly arm for effortless and damage-free assembly of low-profile, UHP and run-flat tires
- Height-adjustable center hole mounting with use of a clamping flange and quick-release nut
- Lateral extractor with double-acting aluminium cylinder and anti-jamming system
- Including wheel lift, quick release tool, pneumatic assembly tool and WDK kit

Additional Information

Rim diameter max.	12 – 26 "
Rim width	4 – 13 "
Max. wheel diameter	1.050 mm
Compressed air connection	10 bar
Bead breaking range	83 – 350 mm
Bead breaker force	2.500 kg
Mounting speeds	6 and 12 U/min
Driving power	0,75 / 0,90 kW
Power supply voltage	3x 400V / C16A
Noise level	70 dB(A)

