

# ATH Frame Lift 30FZ UG

## Product Images

---



## Description

---

- High-quality and robust double scissor lift with hydraulic drive, almost maintenance-free
- Powerful hydraulic unit with load-dependent lowering valve
- Very low drive-over height of only approx. 105 mm
- Suitable for installation and use on the floor and optional floor-level installation (in ground kit)
- Synchronization control via double master and slave systems, safety light barriers and double hydraulic lines
- Full lifting power from the lowest point due to mechanical swivel system
- Emergency lowering system for lowering in the event of a power failure, CE-Stop and acoustic lowering signal
- Ideally suited for paint and body shops, repairs, brake and tire services

## Additional Information

---

|                       |                                    |
|-----------------------|------------------------------------|
| Color                 | anthracite-grey                    |
| Rated load capacity   | 3.000 kg                           |
| Lifting height max.   | 1.900 mm                           |
| Drive-on-height       | 105 mm                             |
| Total platform length | 1.495 – 2.030 mm                   |
| Total platform width  | 600 mm                             |
| Driving power         | 2,6 kW                             |
| Lifting/Lowering time | ca. 50 s                           |
| Power supply voltage  | 3x 400V / C16A                     |
| Concrete strength     | min. C20/25 2.500 x 2.500 x 180 mm |

