

ATH Four Lift 55A

Product Images



Short Description

4-post lift for passenger cars and vehicles with long wheelbase, capacity 5500 kg, perfect lift for wheel alignment

Description

- High-precision manufacturing by laser cutting and robotic welding
- Robust and less sensitive hydraulic drive, almost maintenance-free
- For passenger cars and vehicles with long wheelbase; platform length 5,50 m, one platform is continuously adjustable
- Can be used universally with flat platforms and rails for an optional rolling jack
- Perfect lift for wheel alignment with recess for turn plates in the front and already installed sliding plates in the back; also perfect for headlamp beam setting due to the notch system for adjusting the platforms
- Only drive-on and repair, no lifting arms
- 2-piece drive-on ramps hinged, perfect for lowered vehicles
- Lifting and lowering with push button control
- Pneumatic unlocking of notches, slack rope protection, emergency lowering system for lowering in case of power failure, CE stop and signal sound
- Perfect lift for automotive repairs and headlamp beam setting

Additional Information

Color	anthracite-grey / black
Rated load capacity	5,5 t
Lifting height max.	1.890 mm
Drive-on-height	246 mm
Total platform length	5.190 mm
Total platform width	490 mm
Driving power	2,2 kW
Lifting/Lowering time	ca. 45 s
Power supply voltage	3x 400V / C16A
Concrete strength	min. C20/25 7.400 x 3.900 x 200 mm

